

DECLARATION OF PERFORMANCE

1. Unique identification code of the product type: DPC

2. Serial number or any other element allowing identification of the construction product:
****DPC****

3. Use:

A damp-proof course (often abbreviated to DPC) is a horizontal barrier in a wall designed to resist moisture rising through the structure by capillary action.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Deschacht Plastics Belgium nv
Antwerpsesteenweg 1068 · B-9041 Gent-Oostakker

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not revelant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: Notified body „Statybos produkcijos sertifikavimo centras“ performed the inspection of the manufacturing plant and issued the certificate of conformity of the factory production control (1397-CPD-0199).

8. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Thickness, my	(270-500)±15%	EN 1849-2:2010
Width, mm	(100-1200)±5%	EN 1848-2
Tensile strength, MPa -machine direction -cross machine direction	>14 >12	EN 12311-2:2010
Elongation at break, % -machine direction -cross machine direction	>300 >400	EN 12311-2:2010
Resistance to impact, mm	200	EN 12691:2006
Resistance to water penetration	waterproof	EN 1928:2001

9. The users should take own decisions in terms of product adequacy for the application. Supplier does not carry any responsibility in case product is handled in wrong way or in the applications that are not confirmed by the supplier.

Head of Quality control department
Dated 12.08.2014